

Benefits of using Roth X-PERT S5®

Ultimate System Protection

The five-layer design ensures that the EVOH oxygen barrier is protected and remains intact, safeguarding your radiant heating system. X-PERT S5® comes with a limited lifetime warranty.

Unsurpassed Flexibility

X-PERT S5® saves you time and money even at low temperatures, which improves installation efficiencies.

Reduce pressure loss & deposit formation

Roth X-PERT S5® pipe has excellent smoothness.

Environmentally Friendly

Unlike any other heat pipe, X-PERT S5® is fully recyclable.

Product Specifications

Pipe Dimensions and Tolerances

X-PERT S5® PE-RT pipe is manufactured and tested according to the guidelines set forth in ASTM F2623.

Joining

X-PERT S5® PE-RT may be joined using insert fittings and clamps certified to ASTM F-877, F-1807, or F-2159. It may also be joined using thermal fusion methods eliminating the need for mid-loop mechanical fittings.

Maximum Operating Temperature and Pressure

200 PSI at 73°F

100 PSI at 180°F

Superior Material

X-PERT S5® Polyethylene Copolymer Resin is an ethylene/octane-1 copolymer. It has a unique molecular structure with a controlled side chain distribution, which provides a combination of excellent stress crack resistance and Long Term Hydrostatic Strength properties.

Oxygen Diffusion Standard

DIN 4726

Chemical Tubing Resistance Chart

DIN 8075 Standard

Call 1.888.266.7684 or visit www.roth-america.com
for additional information and product lines.



Roth, a family-owned business established in Germany over 60 years ago, now operates in over 40 countries worldwide with \$250 million in sales and 1,100 employees. The North American division operates two manufacturing plants in upstate New York. Roth specializes in environmentally-friendly products that produce, distribute and store energy for the finest homes.



ENERGY PRODUCTION:

Solar and Heat Pump Systems

ENERGY STORAGE:

Septic, Cistern, Rainwater Collection and Oil Storage Tanks

ENERGY DISTRIBUTION:

Radiant Floor Heating and Pex-c Plumbing Systems

Roth Industries, Inc. North American Corporate Office

P.O. Box 245, Syracuse, NY 13211

Toll Free US: 888.266.7684 CAN: 800.969.7684

P: 315.755.1011 F: 315.755.1013 info@roth-usa.com service@roth-canada.com www.roth-america.com


X-PERT S5[®]

5-Layer PE-RT Pipe With Oxygen Barrier

ENERGY DISTRIBUTION



An evolution in polymer technology
for hydronic heating



Environmentally-friendly products that produce, distribute
and store energy for the most efficient homes.



PE-RT is to PEX what PEX was to copper 20 years ago. X-PERT S5[®] is the next evolution in polymer technology for hydronic heating.



X-PERT S5[®] 5-LAYER PE-RT PIPE WITH OXYGEN BARRIER


- Polyethylene of raised temperature (PE-RT)
- No cross-linking required, no waste, no chemicals
- Pioneered in Europe and actively used for over 20 years
- DOWLEX™ 2344 Polyethylene Copolymer Resin
- 100% Recyclable material
- Made in the USA

PIPES CAN BE USED FOR NON-POTABLE HOT AND COLD WATER SYSTEMS, INCLUDING:

- radiant floor heating systems
- radiator connections
- baseboard hot water connections
- heating/cooling applications
- snow melt applications

Roth X-PERT S5[®] pipe is the ideal choice for domestic and industrial radiant heating systems in North America.

Environmentally-friendly products that produce, distribute and store energy for the finest homes.




PROVEN HISTORY

PE-RT pipes have been used in European markets for more than twenty years with exceptional results. Roth X-PERT S5[®] pipe is made with DOWLEX™ 2344 Polyethylene Copolymer Resin, which offers the traditional benefits of polyethylene resin along with excellent high temperature resistance. The result is the next generation of radiant heating pipe.

Roth X-PERT S5[®] pipe delivers excellent long-term hydrostatic design strength, without the need for cross-linking. This increases flexibility, resulting in potential installation savings. Roth X-PERT S5[®] also has excellent surface smoothness for improved flow properties and is produced using state of the art equipment .

The five-layer pipe consists of a layer of ethylene vinyl alcohol polymer (EVOH) sandwiched between two layers of Polyethylene Copolymer Resin and two layers of adhesive. This structure provides the outstanding long-term hydrostatic design strength demanded by hydronic heating applications. The outer layer of Roth X-PERT S5[®] also provides a protective shield for the oxygen barrier. This ensures that the radiant heating system has the best protection available against oxidation due to oxygen permeation of the piping system.

Roth X-PERT S5 ® Five-Layer Design



The five-layer pipe consists of a layer of ethylene vinyl alcohol polymer (EVOH) sandwiched between two layers of Polyethylene Copolymer Resin and two layers of adhesive. This structure provides the outstanding long-term hydrostatic design strength demanded by hydronic heating applications.

Material Properties

Physical Properties	Values	Unit	Test Method
Density	58.745	lb/ft ³	ASTM D-792
Thermal Conductivity @ 140° F	2.7734	BTU (h.ft ² F/ in)	DIN 52612-1
Thermal Expansion Coefficient °F (680 °F to 158°F)	0.0000394		DIN 5375
Oxygen Diffusion Rate with O ₂ Barrier at 100°F	Better than .0002	Mg/in ² x24h	DIN 4726
Oxygen Diffusion Rate with O ₂ Barrier at 180°F	Better than .00004	Mg/in ² x24h	DIN 4726
Mechanical Properties	Values	Unit	Test Method
Tensile Yield	2,988	Psi	ISO 527-2
Ultimate Tensile	5,221	Psi	ISO 527-2
Percentage fo Elongation	760	%	ISO 527-2
Modulus of Elasticity	138,511	Psi	ISO 178

Size Specifications

Tube	O.D.	W.T.	I.D.	Weight (lb./ft.)	Water Content (gal/ft.)
3/8"	.500	.070	.360	.042	.0053
1/2"	.625	.070	.485	.054	.0096
5/8"	.750	.083	.584	.076	.0139
3/4"	.875	.097	.681	.103	.0189
1"	1.125	.125	.875	.167	.0312